



MI 4620

4620D INTERNAL RECORDER INTERFACE

USERS GUIDE

COMCODE: 700 379 399



Description

The MI4620 recorder interface module provides an analog audio output of voice conversations for recording purposes. The module fits within the set and must be factory installed.

Features

The MI4620 records from the handset, speakerphone, and headset (if equipped).

A beep tone alerts both parties that the conversation is being recorded every 15 seconds. This feature may be switch on or off by the user.

Connections

Connect the MA1 cable (or other cable equipped with 1/8" mini phone plug) to the jack on the back of the set. Connect the other end of the cable to the recording device.

Operation

The MI4620 operates automatically any time the voice terminal is used. The user can turn the beep tone alert on or off with a toggle switch located on the back of the set behind the line jack. It may be necessary to unplug the line jack to operate the switch.

Specifications

BEEP TONE 1400Hz; 200ms burst, 15 ssec interval.

ACCESSORIES INCLUDED

1ea. MA1 cable: 3ft length. 1/8" mini phone plug to 1/8" mini phone plug. For use with portable cassette recorders or similar devices with 1/8" jack.



Starcom Incorporated

3303 North Dixie Highway
Boca Raton, FL. 33431

phone: (561) 392-7001 ★ fax: (561) 392-7003 ★ email: sales@starcom-inc.com ★ internet: www.starcom-inc.com